

| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 600



Technical data

| Modularity: | Тор |
|-------------------------------------|-------------|
| Dimension (mm): | 300x600x300 |
| Total gas power (Kcal/h): | 4472 |
| Total gas power (kW): | 5,2 |
| Cooking zone dimensions 1 (LxD mm): | 296x470 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,054 |
| Packing dimensions (mm): | 376x695x596 |
| Gross weight (kg): | 35 |
| Gross volume (m3): | 0,156 |

Features

| Made of AISI 304 stainless steel with a thickness of 8/10 mm |
|--|
| Satin chrome |
| Smooth |
| Knobs are made from a sturdy heat-resistant polymer blend |
| Made in a single piece, which facilitates the alignment of the modules |
| Removable and dishwasher safe |
| Satin chrome plate |
| On two sides |
| Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |
| |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.




Fry top gas, piastra cromo satinato liscia, top

Gas griddle with satin chrome smooth plate Top with deep funnel in AISI 304 stainless steel; covering in AISI 430 stainless steel thickness 8/10; bottoms and internal parts in anti-corrosion material (aluminised sheet metal). Cooking hotplate in satin chrome steel with high thermal conductivity for even temperature distribution. Provided with front groove, extractable drawer for grease collection and splash guard on three sides. Steel burner with pilot burner with piezoelectric ignition. Gas supplied by means of thermostatic safety valve with thermocouple. 1 burner x 5.2 kW. - Total power 5.2 kW - Plate dimensions 295x470 mm.

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.