



| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 650

Model: F65/110CFGB Cod: MP01032112001

Technical data

| Modularity: | Gas oven |
|------------------------------|---------------|
| Dimension (mm): | 1100x650x850 |
| Oven dimension (mm): | 555x540x270 |
| Total gas power (Kcal/h): | 26484 |
| Total gas power (kW): | 30,8 |
| Oven type: | Static oven |
| Oven power (kW): | 5 |
| Oven temperature range (°C): | 150-300 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,608 |
| Packing dimensions (mm): | 1176x776x1180 |
| Gross weight (kg): | 124 |
| Burner power 1 (kW): | 5 |
| Burner power 2 (kW): | 3,6 |
| Burner power 3 (kW): | 5 |
| Burner power 4 (kW): | 3,6 |
| Burner power 5 (kW): | 5 |
| Burner power 6 (kW): | 3,6 |
| Gross volume (m3): | 1,077 |

Features

| Piezo ignition available in cast iron with single crown brass burner cap |
|--|
| In cast iron with long spokes |
| Made of AISI 304 stainless steel with a thickness of 10/10 mm and removable enamelled containers |
| Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid anti- leakage washer |
| Brushed aluminum finish |
| Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |
| |


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Gas range enamelled containers, 6 burners, gas oven

Gas range, 6 burners with gas oven Top in AISI 304 stainless steel thickness 8/10; covering in AISI 430 stainless steel 8/10; bottoms and internal parts in AISI 430 steel;internal reinforcements made of anti-corrosion material. (aluminised sheet metal). Hob equipped with 6 burners (3x3.6 kW + 3x5 kW) - total power 25.8 kW. Bowls in enamelled steel that can be extracted for easy cleaning. Pan supports for hobs in acid-resistant enamelled cast iron. Safety gas valve cocks with thermocouple. Piezoelectric burner ignition. Internal oven dimensions 53x54x28h cm. Oven rack dimensions 53x53cm. Double wall thermally insulated oven door. Thermal insulation of oven chamber. Heating takes place by means of a stabilized flame with piezoelectric ignition; the supply of gas takes place by means of a safety thermostatic valve with thermocouple. Temperature adjustment from 150° to 300°C. Piezoelectric ignition of oven burner. Total power 5 kW. Total power 30.8 kW.

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.