



| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 700

Model: F70/70TPFG Cod: MP01052113002

Technical data

| Modularity: | Gas oven |
|------------------------------|--------------|
| Dimension (mm): | 700x700x850 |
| Oven dimension (mm): | 555x540x270 |
| Total gas power (Kcal/h): | 12038 |
| Total gas power (kW): | 14 |
| Whole-plate power gas (kW): | 8,2 |
| Oven type: | Static oven |
| Oven power (kW): | 5 |
| Oven temperature range (°C): | 150-300 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,417 |
| Packing dimensions (mm): | 776x776x1180 |
| Gross weight (kg): | 103 |
| Gross volume (m3): | 0,711 |

Features


| Grill: | Cast-iron with brass single- and double-crown burner with pilot |
|--------------|---|
| Working top: | Made of AISI 304 stainless steel with a thickness of 10/10 mm |
| Knobs: | Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer |
| Kit Gas: | Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Gas solid top range on gas oven. Top made of AISI 304 stainless steel thickness 8/10; covering in AISI 304 stainless steel thickness 8/10; bottoms and internal parts in AISI 430 steel; internal reinforcements made of anti-corrosion material (aluminised sheet metal). Steel full plate featuring high-performance and equipped with central pull-out ring. Heating takes place by means of the high-power cast iron central burner, with piezoelectric ignition pilot burner. Gas is supplied by means of a safety valve with thermocouple. Static gas oven in enamelled steel with double wall isolated door on hinges with balancing springs. The thermally insulated chamber is equipped with 3-position side rack supports which can be extracted for cleaning. Heating takes place by means of stabilized flame burner with piezoelectric ignition; gas is supplied by means of a thermostatic safety valve with thermocouple. Temperature adjustment from 150° to 300°C. Internal dimensions 530x540x280h. mm. - 1 rack 530x530 mm included. Full plate 1 burner 8.2 kW. Total power 5 kW. Total gas power 13.2 kW

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.