



Client	Quantity
Project	Position

## **ROC 900**

Model: R90/120TPPGFB/P Cod: MP01054114057

## **Technical data**

Modularity:	On cabinet with doors
Dimension (mm):	1200x900x870
Total gas power (Kcal/h):	28376
Total gas power (kW):	33
Whole-plate power gas (kW):	7
Gas connection:	1/2"
Packing dimensions (mm):	1280x1026x1109
Gross weight (kg):	158
Burner power 1 (kW):	5,5
Burner power 2 (kW):	7,5
Burner power 3 (kW):	5,5
Burner power 4 (kW):	7,5
Gross volume (m3):	1,456

## **Features**

with a thickness of 20/10 mm  Knobs: Made of aluminum with IPX5 water protection  Handles: The brushed aluminum handles allow for a secure and sturdy gr with a ergonomic lines  Flue: Removable made of cast iron		
Water protection  Handles: The brushed aluminum handles allow for a secure and sturdy gr with a ergonomic lines  Flue: Removable made of cast iron  Kit Gas: Natural gas conversion kit 30/5	Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
allow for a secure and sturdy gr with a ergonomic lines  Flue: Removable made of cast iron  Kit Gas: Natural gas conversion kit 30/5	Knobs:	
Kit Gas: Natural gas conversion kit 30/5	Handles:	allow for a secure and sturdy grip
· tatarar gas sorrer sister int so, s	Flue:	Removable made of cast iron
G20)	Kit Gas:	,


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Gas solid top, 4 burners enamelled containers, on cabinet with doors

Gas solid top range, 4 burners enamelled containers, on cabinet with doors. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10 designed for flush alignment. Rear flue made in enamelled cast-iron. Cooking plate made in extrathick cast iron with extractable central plate. The central zone can reach 500°c while decreasing awards (to 300 °C). Heating by cast iron burner with 7 kW power. Gas supply by means of safety tap with pilot flame and safety thermocouple. Iignition by means of piezoelectric device with waterproof cap. Plate dimensions 380x710. Equipped with high-power cast iron/brass rapid burners with containers in enamelled steel that can be extracted for easy cleaning. nr.2 burner 7.5 kW and nr.2 burner 5.5 kW. Special design knobs to avoid water penetration in the control panel. Adjustable feet. IPX5 protection rating. Gas total power 33 kW.

## **Technical draw**







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.