



| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 700

Model: F70/70FTG/LR/T

Market: Extra UE

Cod: MP01372113013

Technical data

| Modularity: | Тор |
|-------------------------------------|-------------|
| Dimension (mm): | 700x700x300 |
| Total gas power (Kcal/h): | 9803 |
| Total gas power (kW): | 11,4 |
| Cooking zone dimensions 1 (LxD mm): | 696x520 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,147 |
| Packing dimensions (mm): | 776x776x636 |
| Gross weight (kg): | 74 |
| Gross volume (m3): | 0,383 |

Features

| Working top: Made of AISI 304 stainless steel with a thickness of 10/10 mm Material of plate: Mild steel Knobs: Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) | | |
|---|--------------------|---|
| Knobs: Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas | Working top: | |
| heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas | Material of plate: | Mild steel |
| Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas | Knobs: | heat-resistant polymer blend and are equipped with liquid anti- |
| m/bar (tested with natural gas | Plate: | In mild steel |
| | Kit Gas: | m/bar (tested with natural gas |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Gas griddle, 2/3 smooth 1/3 ribbed mild steel plate, top

Gas griddle plate 2/3 Smooth 1/3 grooved top version. Top made of AISI 304 stainless steel thickness 8/10; covering in AISI 304 stainless steel thickness 8/10; external reinforcements made of anti-corrosion material (aluminised sheet metal); bottoms and internal parts in AISI 430 steel; flue cover in enamelled steel. Equipped with two independent cooking zones. Provided with front groove, extractable drawer for grease collection and splash guard on three sides. Equipped with burners with pilot burners with piezoelectric ignition. Gas supplied by means of safety valve with thermocouple. - 2 burners x 5.7 kW Total power 11.4 kW Plate dimensions 695x550 mm. Can be set up on bridge system, on open cabinet or with doors.

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.