



Client	Quantity
Project	Position

FUN 700

Model: F70/70FTG/LR/T

Market: Extra UE

Cod: MP01372113013

Technical data

Modularity:	Тор
Dimension (mm):	700x700x300
Total gas power (Kcal/h):	9803
Total gas power (kW):	11,4
Cooking zone dimensions 1 (LxD mm):	696x520
Gas connection:	1/2"
Net volume (m3):	0,147
Packing dimensions (mm):	776x776x636
Gross weight (kg):	74
Gross volume (m3):	0,383

Features

Working top: Made of AISI 304 stainless steel with a thickness of 10/10 mm Material of plate: Mild steel Knobs: Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas G20)		
Knobs: Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas	Working top:	
heat-resistant polymer blend and are equipped with liquid antileakage washer Plate: In mild steel Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas	Material of plate:	Mild steel
Kit Gas: Natural gas conversion kit 30/50 m/bar (tested with natural gas	Knobs:	heat-resistant polymer blend and are equipped with liquid anti-
m/bar (tested with natural gas	Plate:	In mild steel
	Kit Gas:	m/bar (tested with natural gas

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Gas griddle, 2/3 smooth 1/3 ribbed mild steel plate, top

Gas griddle plate 2/3 Smooth 1/3 grooved top version. Top made of AISI 304 stainless steel thickness 8/10; covering in AISI 304 stainless steel thickness 8/10; external reinforcements made of anti-corrosion material (aluminised sheet metal); bottoms and internal parts in AISI 430 steel; flue cover in enamelled steel. Equipped with two independent cooking zones. Provided with front groove, extractable drawer for grease collection and splash guard on three sides. Equipped with burners with pilot burners with piezoelectric ignition. Gas supplied by means of safety valve with thermocouple. - 2 burners x 5.7 kW Total power 11.4 kW Plate dimensions 695x550 mm. Can be set up on "bridge system", on open cabinet or with doors.

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.