

| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 700

Model: F70/40FTG/SL/T Cod: MP01372113027



Technical data

| Modularity: | Тор |
|-------------------------------------|-------------|
| Dimension (mm): | 400x700x300 |
| Total gas power (Kcal/h): | 4902 |
| Total gas power (kW): | 5,7 |
| Cooking zone dimensions 1 (LxD mm): | 396x520 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,084 |
| Packing dimensions (mm): | 477x776x612 |
| Gross weight (kg): | 48 |
| Gross volume (m3): | 0,227 |

Features

| Working top: | Made of AISI 304 stainless steel with a thickness of 10/10 mm |
|--------------------|--|
| Material of plate: | Satin chrome |
| Plate finish: | Smooth |
| Knobs: | Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid anti- leakage washer |
| Plate: | Satin chrome plate |
| Kit Gas: | Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Gas griddle, smooth satin chrome plate, top

Gas griddle with satin chrome smooth plate top version. Top made of AISI 304 stainless steel thickness 8/10; covering in AISI 304 stainless steel thickness 8/10; external reinforcements made of anti-corrosion material (aluminised sheet metal); bottoms and internal parts in AISI 430 steel; flue cover in enamelled steel. satin chrome steel plate with high thermal conductivity for even temperature distribution. Provided with front groove, extractable drawer for grease collection and splash guard on three sides. Equipped with steel burner with pilot burner with piezoelectric ignition. Gas supplied by means of thermostatic safety valve with thermocouple. - 1 burner x 5.7 kW. Plate dimensions 395x550 mm. Can be set up on "bridge system", or on neutral base with optional doors

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.